



AFRIMAT[®]

Name of Quarry:	Smalbaar		
Town or City:	Rawsonville		
Telephone number:	023 349 1967		
Fax number:	N/A		
Address:	Erf 2 Rawsonville		
Email:	smalbaar@afrimat.co.za		
GPS Coordinates:	33°41'29.3" S	19°18'54.7" E	
Quarry Manager:	Deon Uys	Cell number:	082 829 1815

Please indicate the material that your quarry manufactures or that you will be able to supply.

Road Stone	✓
19 mm	
13,2 mm	
9,5 mm	
6,7 mm	
4,75 mm	
2-4 Grit	

Concrete Stone	✓
53 mm	
37,5 mm	
26,5 mm	✓
19 mm	✓
13,2 mm	✓
9,5 mm	✓
6,7 mm	✓
4,75 mm	

Ballast	✓
63 mm	
53 mm	

Base	✓
G 1	
G 2	
G 3	
G 4	

Subase	✓
G 5	
G 6	
G 7	✓

Sand	✓
Concrete Sand	✓
Plaster Sand	✓
Filling Sand	✓

Other	✓
Gabion	✓
Riprap	
13,2 mm Gravseal	
Crusher Sand	✓
Slurry Dust	
Ralumac	
13,2 mm Drainage	✓
UTFC Stone	

Other	✓
Filling – 100 mm	
ROC with high PI	
UTFC Dust	

Geological Deposit: (Type of material)	Quartzitic Sand Stone
Relative Density, %:	
Water Absorption, %:	
Alkali Reactivity Expansion, %:	
Durability – Ethylene Glycol, %:	
Polished Stone Value:	
Los Angeles Abrasion, %:	
Silica Content, %:	

Disclaimer

The above data is based on continuous testing and is therefore regarded as average results and should not be used for calculation purposes. Please contact Afrimat technical services at johan.burger@afrimat.co.za or call 023 342 6026 for the latest up to date test results.